



Logistorage

Cube 120-027

Cube 120-027

Caricatore Solare

Potenza Massima in ingresso del pannello

Tensione Massima in ingresso

Corrente Massima in ingresso

100Wp

36 - 40 V DC

10 A

87 %

Efficienza

Batterie

Tipologia Batterie

Tensione Nominale pacco batterie

Capacità nominale (Ah)

Capacità nominale (Wh)

AGM

12 V DC

22 Ah

264 Wh

Parametri di Sistema

Protezione

Lampade

Protezione al sovraccarico

Protezione alla Sovratemperatura

Sovraccarichi , carica ,scarica e carico

LED

35 A per 5 sec.

>55 °C

Dati Generali

Temperatura Range di lavoro

Temperatura di esercizio ottimale

Dimensioni (LxWxH cm)

Peso (kg)

-5/+50 °C

20 °C

30 x 13 x 20

6 Kg

Carichi Consigliati

- 5/6 LAMPADINE 12 Volt DC - 3 W (8 ore di autonomia)
- 1 Carica telefono
- 1 Carica Pc





ogistorage

Cube 120-027

Cube 120-027

Solar Charger

Max Pv. Array Power

Max. Pv input Voltage

Max. Pv input Corrent

100Wp

36 - 40 V DC

10 A

Efficiency

87 %

Battery

Battery type

Nominal voltage battery pack

Nominal capacity (Ah)

Nominal capacity (Wh)

AGM

12 V DC

22000 Ma

264 Wh

System Parameter

Protection

Indicators

Over load protection

Over temperature protection

Overload, charge, discharge and load

LED

35 A for 5 sec.

>55 °C

General Specifications

Operating temperature Range

Optimum operating temperature

Dimension (LxWxH cm)

Weight (Kg)

-5/+50 °C

20 °C

30 x 13 x 20

6 Kg

Tools

- 5/6 Light Bulbs 12 Volt DC - 3 W (8 hours of battery)
- 1 Phone Charge
- 1 Laptop Charge

